

TECHNICAL DATA SHEET

LDPE HONEY

PRODUCT DESCRIPTION:

- Honey LDPE (Low-Density Polyethylene) granules, primarily intended for film applications.
- Produced from high-quality European origin post-industrial 90/10 and 95/5 grade LDPE film scrap.

MANUFACTURING PROCESS:

- Standard processing includes:
 - Crushing
 - Triple-stage washing in separate pools
 - Agglomeration
 - Double-stage extrusion into granules

Properties	Unit	Value
Melt Flow Index (MFI) Range (190°C, 2.16 kg)	g/10 min	0.70 - 1.10
Density	g/cm ³	0.91 - 0.93
Granule Size	mm	2-6
Volume Available	ton/month	400
Regular Mesh Size	2 pieces of 65 mesh and 2 pieces of 100 mesh	
Ash Content	≤ 3%	
Elongation at Break	Minimum 800%	
Scrap Type	European Origin 90/10 and 95/5 grade film scrap	
Packing	Big Bags	
Application	Film Grade	

Note: The above properties values are not to be construed as specifications.

Address :Sarıhamzalı Mah. 47097 Sk.Kemal Deniz Geri
Dönüş.Sit. No:1/P Seyhan/Adana/TÜRKİYE

Phone :+90 539 306 20 00
Phone :+90 530 960 01 65

Mail :info@bereketplast.com

Web Site :bereketplast.com